

Panafax®
UF-6000

dependable

Plain Paper Laser Fax



Panasonic **ideas for life**

Features

- Autodialer One-touch: up to 32 stations
Abbreviated: up to 100 stations
Maximum digits for telephone number: 36 digits
 - Program keys (up to 4 Programs)
 - Multi-Tasking Operation
 - Directory Search Dialing
 - Directory Sheet Print
 - Intelligent Redial
 - Chain Dialing
 - Distinctive Ring Detector (DRD)
 - Quick Memory Transmission
 - Multi-station Transmission (up to 144 stations)
 - Automatic Memory Re-transmission
 - Deferred Transmission
 - Deferred Multi-station Transmission
 - Priority Direct Transmission
 - Edit File Mode with View Mode
 - Automatic Cover Sheet
 - Receive to Memory
 - Substitute Reception
 - Selective Reception
 - Number of memory job files (Max. 10 files)
 - Fax Forward
 - Polling / Multi-station Polling (up to 144 stations)
 - Deferred Polling/Deferred Multi-Station Polling
 - Memory Polling Transmission (1 file)
 - Confidential Mailbox*¹ (10 mailboxes)
 - Password Transmission/Reception*¹
 - ITU-T Sub-address Transmission
 - Panasonic Super Smoothing (Fax/Copy)
 - 64-Level Halftone
 - Automatic/Fixed Reduction
 - Overlapping Print
 - Collation Stack
 - Verification Stamp
 - Communication Journal with image data
 - Header/Total Page Print
 - Transaction Journal with view mode
 - Fax Access Code (Fax Lock)
 - PIN Code Access
 - Fax/Tel Auto Switch
 - External TAM Interface
 - Remote Reception
 - Multi-Purpose LCD Display (20 x 2 lines)
 - Multiple Copy with Sorting (up to 99 copies)
 - Reduction Copy
 - Energy Saver
 - Remote Diagnostics
 - Check & Call Function
-
- Printer Interface
 - Scanner Interface
 - PC-Fax software ("Panafax Desktop")
 - Document Manager
 - Document Viewer with Annotation Function
 - Phone Book Editor
 - Configuration Editor
 - Status Monitor

Options

- 250-sheet Universal Paper Feed Unit (UE-409070)
- Handset Kit (UE-403176)

Consumable

- All-In-One Print Cartridge (toner/developer/drum)
(UG-5510) 9,000-page Toner*¹⁰

UF-6000 Specifications

Compatibility	ITU-T Group 3, ECM
Modem Speed	33,600 - 2,400 bps with automatic fallback
Coding Scheme	MH/MR/MMR
Transmission Speed* ²	Approx. 3 sec.
Document Size	Max. 10.1" x 78.7" (257 mm x 2000 mm) (with operator's assistance)
	Min. 5.8" x 5.0" (148 mm x 128 mm)
Effective Scanning Width	8.3" (212 mm)
Automatic Document Feeder Capacity* ³	50 sheets
Document Thickness	Single sheet: 0.0024" - 0.0060" (0.06 - 0.15 mm)
	Multi-sheet: 0.0024" - 0.0039" (0.06 - 0.10 mm)
Scanning Resolution (Fax)	Standard: 203 dots/inch x 98 lines/inch (8 dots/mm x 3.85 lines/mm)
	Fine: 203 dots/inch x 196 lines/inch (8 dots/mm x 7.7 lines/mm)
	Super Fine: 203 dots/inch x 391 lines/inch (8 dots/mm x 15.4 lines/mm)
	406 dots/inch x 391 lines/inch* ⁴ (16 dots/mm x 15.4 lines/mm)
Scanning Speed* ⁵	Approx. 2.8 sec. (Letter, Standard mode)
Recording Method	Laser printing on plain paper
Printing Speed* ^{6,7}	6.5 ppm
Recording Paper Size	Letter / Legal / A4, cut-sheet on plain paper
Effective Recording Width	8.2" (208 mm) (Letter)
Recording Paper Capacity	250 sheets (20 lb., 75 g/m ²) With optional cassette: Approx. 500 sheets max. total
Recording Resolution	Fax / Copy 406 dpi x 391 dpi
	Printer 600 dpi x 600 dpi
Image Memory Capacity* ⁸	8 MB (Approx. 480 pages)
Printer / Scanner Interface	Bi-directional Parallel (IEEE1284)
Scanner Driver	TWAIN
Scanning Resolution (PC)* ⁴	400 dots/inch x 400 dots/inch
Power Requirements	AC 120 V, 60 Hz
Power Consumption	Max. Approx. 470 W
	Sleep mode: 1.2 Wh
Dimensions (W x D x H)* ⁹	14.6" x 18.7" x 9.8" (370 mm x 474 mm x 250 mm)
Weight* ⁹	20 lb. (9.0 kg) (Excluding consumable supplies and optional equipment)

*¹ Panafax proprietary features work only with selected Panafax machines.

*² Transmission time applies to memory transmission of text data using only ITU-T Image No. 1 between the same models at maximum modem speed. Transmission time may vary in actual usage. Usually public telephone lines can only support communications speeds of 28.8 Kbps or lower. Via PBX, transmission speed may fall back to a lower speed.

*³ Operating environment 20°C 50% Relative Humidity. Set the documents as stairs shape.

*⁴ Interpolated resolution (Optical Resolution: 203 dots/inch x 391 lines/inch)

*⁵ Scanning speed applies to the feeding process from the top to the end of a single page test chart.

The time for the feeding process does not include the time that it takes for the top edge of the page to reach the scanning point and page ejection. Time for entire storing process is not applied.

*⁶ Speeds are contingent upon applications, machine configuration, and status. Individual speeds may vary.

*⁷ In multiple copy mode excluding the first copy.

*⁸ Based on ITU-T Image No. 1 scanned in Standard mode.

*⁹ Dimensions and weight are approximate.

*¹⁰ Based on ITU-T Image No.1 scanned in multiple copy mode, set on fine resolution and using letter size recording paper. Yield may vary according to operating conditions and environment where the machine is installed.

Microsoft®, Windows® and Windows NT® are registered trademarks of Microsoft Corporation.
All other brand or product names are the property of their respective holders.

Design and specifications are subject to change without notice.

Dimensions



As an ENERGY STAR® Partner, Panasonic has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.

ISO 9001 Quality Management System

Our business processes which produce document, information and network products, from manufacturing to marketing, conform to ISO 9001 Quality Management Systems standard. Design, development, manufacture, installation, repair and maintenance of document, information and network products, their associated devices and consumables. In addition, the plants outside Japan have acquired ISO 9001 certification.



Panasonic®

Panasonic Digital Document Company
Unit of Panasonic Corporation of North America
Two Panasonic Way, Secaucus, NJ 07094
For a local dealer, please call 1-800-742-8086
panasonic.com/office